



SPECIFICATION	OPTIONS AVAILABLE
VERTICAL PLATFORM LIFT	KEY SWITCH DOOR CALL POINTS
FOR USE BY PERSONS WITH IMPAIRED MOBILITY	KEY ISOLATE DOOR CALL POINTS
ONLY LOADING TO 400kg, TWO PERSON OCCUPANCY	STAINLESS STEEL DOOR HANDLES
WITH FULLY ENCLOSED SHAFT	PIT
PLATFORM SIZE 1480mm x 1000mm	SPLIT MAST
	POWERED DOOR ACTUATORS REAR CLADDING PANELS
	STAINLESS STEEL GRAB RAIL
	MAST SUPPORT BRACKETS
	FOLD DOWN PLATFORM SEAT
ELECTRICAL REQUIREMENTS	AUTODIALER
- LIET DOWED CUDDLY	PLATFORM AUDIBLE / VISUAL ANN.
₹1 LIFT POWER SUPPLY 1 PHASE 230V 20A or	INDUCTION LOOP
3 PHASE 415V 10A	AUDIBLE ANN. ON LANDING
Z2 CEILING LIGHT POWER SUPPLY	VISUAL ANN. ON LANDING
For the supply the sup	SUPPLEMENTARY VISUAL ALARM
LIETINO DEAM / DOINT DECLUDENTA	GLAZING
LIFTING BEAM / POINT REQUIREMENTS	SIDE A
J LIFTING BEAM / POINT REQUIRED RATED AT 500kg SWL	SIDE B
	A J.J.SELFRIDGE 20 APR 09 ORIGINAL ISSUE ISSUE DRN./DATE CHANGE DETAILS CLIENT
DRAWING APPROVAL	- scale: 1:30
	DRAWING NO: $K-TYP14$
	Dalby
	HARRY DALBY ENGINEERING LTD
DRAWING APPROVED BY DISTRIBUTOR SIGN DATE/	GLOUCESTER CRESCENT WIGSTON LEICESTER LE18 4YQ TEL: 0116 291 6000 FAX: 0116 291 6001
DRAWING APPROVED BY CLIENT	THIS DRAWING IS ISSUED SOLELY ON THE UNDERSTANDING THAT IT IS COPYRIGHT AND CONFIDENTIAL. IT MAY NOT BE USED OR REPRODUCED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY
SIGN DATE/	THIRD ANGLE PROJECTION A.3